

WOOD FUELED BOILER FINANCIAL FEASIBILITY USER'S MANUAL

TABLE OF CONTENTS

Introduction	1
Important Things to Keep in Mind	1
Initial Assessment	1
Overview	1
Getting Started	1
Fuel Cost Estimations for Current	
or Alternate Fuels	2
Fuel Cost Estimations Summary	2
Annual Fuel Costs Estimation	3
Comparison of Systems	
Comparison of Systems	3
Comparison of Systems Alternate (Non Wood or Bark)	3
Comparison of Systems Alternate (Non Wood or Bark) Fueled System	3
Comparison of Systems Alternate (Non Wood or Bark) Fueled System Wood or Bark Fueled System	3
Comparison of Systems Alternate (Non Wood or Bark) Fueled System Wood or Bark Fueled System Summary: Average Annual Fuel Cost	3 4
Comparison of Systems Alternate (Non Wood or Bark) Fueled System Wood or Bark Fueled System Summary: Average Annual Fuel Cost Savings with Wood/Bark Fueled	3 4
Comparison of Systems Alternate (Non Wood or Bark) Fueled System Wood or Bark Fueled System Summary: Average Annual Fuel Cost Savings with Wood/Bark Fueled Boiler System	3 4 4

Simplified Payback Estimation for a Wood or Bark Fueled Boiler System	5
Overview	
Follow-on Preliminary Assessment	
Summary of Inputs Into Analysis for	
Period #2 (First Full Year)	8
Period Inputs Into the	
Economic Model	8
Capital Investments and Simplified	
Estimation of Depreciation	9
Summary	9
Glossary	11
Appendix: Discussion of Sample Wood Fueled Boiler Feasibility Analysis Case.	12

ACKNOWLEDGEMENTS

The authors wish to thank Lew McCreery, Program Leader, USDA Forest Service, Northeastern Area State and Private Forestry for his technical support and the USDA Forest Service Northeastern Area Rural Development program for the financial support that made this effort possible.

How to Get the Program

"Wood Fueled Boiler Financial Feasibility" is a simple spreadsheet program designed for a personal computer. Both the program and the instruction manual can be downloaded from the following web site:

http://forest.wisc.edu/fe_publications.htm

If you do not have access to the web, a copy of the program can be obtained by contacting:

Terry Mace, Forest Utilization and Marketing Specialist WDNR - Division of Forestry One Gifford Pinchot Drive Madison, WI 53726 PHONE: (608) 231-9333 EMAIL: Terry.mace@dnr.state.wi.us

INTRODUCTION

"Wood Fueled Boiler Financial Feasibility" is a spreadsheet program designed for easy use on a personal computer. This program provides a starting point for interested parties to perform financial feasibility analysis of a steam boiler system for space heating or process heat. By allowing users to input the conditions applicable to their current or proposed fuel systems, "Wood Fueled Boiler Financial Feasibility" provides an opportunity to compare wood or bark fuel as alternates to the existing fuel.

This program has been designed for use by most decision-makers seeking basic insight such as annual savings and potential payback of wood fuel. More detailed financial feasibility estimates can also be done on a 20-year period of analysis for those who have greater technical expertise and are more knowledgeable in conducting such analyses.

It is suggested that first-time users read this manual and carefully examine all explanatory text in the spreadsheet related to entries, calculations, and interpretations prior to initial use of the spreadsheet.

Important Things to Keep in Mind

This program is for preliminary financial analysis. More robust models exist for very detailed analysis of biomass projects that extend beyond the scope of this program. This program is not intended to replace technical systems analyses, planning efforts, or pro-forma financial statements prepared by engineering, accounting, or other planning professionals.

INITIAL ASSESSMENT

Overview

The spreadsheet is comprised of step-by-step sections that allow analysis to flow logically – often building on previous sections. Upon opening the program at the top of the spreadsheet, the user will see a brief section of text followed by the calculation sections. Important notes defining variable parameters and assumptions are provided directly in the program. First-time users should read the explanatory text provided in the program.

Getting Started

For those experienced with spreadsheets, using the initial assessment section of the program should be fairly easy with only limited and readily accessible user-specific information. Users follow the step-by-step format outlined in the spreadsheet. The user will need to input estimates of the fuel costs and average boiler load. The program will estimate potential variable cost savings associated with wood fuel. With limited information, most users can do a "quick and dirty" analysis, however, the quality of the results is directly related to the estimates that are used. Consequently, refined estimates will ultimately be desired.

Like any spreadsheet, "Wood Fueled Boiler Financial Feasibility" consists of rows (horizontal cells across the page) and columns (vertical cells up and down the page). Users must enter data where the code "e>" (or "e>>") is shown in column A. "e>" signifies user entries in the initial assessment and "e>>" signifies users entries in the more detailed follow-on analysis. The user enters the data in column C (or multiple columns). In the initial assessment section for instances where the user wishes to ignore a particular fuel – current or alternative – they can simply leave column C blank. Sample numbers are already entered in all entry cells mentioned above. These numbers are provided for illustrative purposes. In many cases, these values represent a reasonable estimate for the value in question (e.g., the estimates of gross Btus per unit of various fuel types and the typical associated boiler efficiency). Fuel costs used in the program examples were reasonable point estimates in the Lake States region of the United States when the program was developed, However, it is likely the user's fuel costs could be significantly different. It is up to the user to examine all data values relative to their circumstances. In particular, all values for fuel costs should be examined and changed by the user if necessary.

Fuel Cost Estimations for Current or Alternate Fuels

The first step in determining the economic feasibility of replacing your operation's current boiler system fuel(s) and replacing it with wood or bark fuel, is to input data regarding your current fuel. The first section of the program allows the user to do this for 11 possible fuel sources. User inputs are required for fuel costs; however, reasonable estimates are provided for Btus per unit and net boiler efficiency. Using these inputs, the program calculates an estimate of the cost per net million Btus for the various fuels. Remember that entries are required for only the existing fuel (or alternate to wood fuel) that you are using or consider using in your analysis. For illustrative purposes only, inputs for all 11 alternate fuels have been entered in the spreadsheet.

For example, scroll down to the section beginning with row 75 "to calculate for natural gas." In this subsection, use **FIGURE 1** (below) for reference.

Note that for each row with "e>" in column A, a value was required to be entered by the user. In this case it was reasonably assumed that \$0.68288 was currently an accurate cost estimate for a therm of natural gas, and that boiler efficiency was 80% (by definition a therm is 100,000 Btus; for other fuels, adjusting the entry may be required). Using the three inputs, a calculation is made by the spreadsheet and appears in bolded text. In this case, it was found that the calculated cost per net million Btus of natural gas was \$8.536. For any current or alternative fuel choices, entries are made in the same way.

Fuel Cost Estimations Summary

The program displays the calculated cost per net million Btus for all of the 11 non-wood fuels. This appears in bold text at the bottom of each fuel analyzed, and again with all fuels displayed together (beginning at cell B112) at the end of this first subsection for quick comparison. NOTE: These calculated fuel values are only meaningful if the three entries have been considered and appropriately modified to represent the users' circumstance.

FIGURE 1

/	Α	В		С
75		to calculate for natural gas		
76 e>	>	What is the cost per therm (or "CCF") for this fuel?	User determines	→→ \$0.68288
77 e>	>	What is the assumed MILLION gross Btu per therm?	values to input	0.1000
78 e>	>	What is the assumed net boiler efficiency in %?		▶ 80.0%
79		Calculated cost per net MILLION Btu of natural gas is:		\$8.536
	1			

e> Signifies needed input

Bold text shows calculated output

(NOTE: Brown lines and text in each figure are not in the spreadsheet. They are presented here to highlight the various aspects of data entry and interpretation).

ANNUAL FUEL COSTS ESTIMATION

The next section of the spreadsheet is titled "PRELIMINARY ECONOMIC ANALYSIS - INITIAL ASSESSMENT - ESTIMATION OF FUEL COSTS PER YEAR, AND COMPARISON OF CURRENT (OR ALTERNATE) FUEL WITH WOOD OR BARK FUELED BOILER SYSTEM" (see row 128).

This section will first develop an estimate of the average cost (annual basis) for current (or alternate) and the wood fuel systems. This will then provide a basis to compare the current (or alternate) fueled system to one that uses wood or bark for fuel.

In this section, users provide the following information for each system:

- The cost per net million Btus of fuel
- The net daily Btus (in million Btus) required for operation
- The number of days that the boiler is used during a one-year cycle

The cost per net million Btus of fuel has already been estimated. The net daily Btus required for operation may be known or it can be estimated if other data is known. This would include the number of days that the boiler is used during a one-year cycle, the boiler efficiency, and the annual fuel bill.

For illustration, consider the section beginning after the explanatory text in row 128 where the entries and calculations appear; see **FIGURE 2** (below).

NOTE: The example shows the calculations made using both ways (if all input data are known or with an estimate based on fuel cost per year). In most cases, one or the other would be entered by the user.

COMPARISON OF SYSTEMS

Information developed thus far allows the program a basis to compare the current (or alternate) fuel with the wood or bark fueled system. Entries are required for both systems as follows.

Alternate (Non-wood or Bark) Fueled System

In this section, simply input the requested data (using the same prompt code as before, "**e**>"). These are the values that were obtained previously and provided in bold text.

FIGURE 2

	А	В				
139		to calculate for current (or alternate) system if above data are known:				
140 e	2>	What is the cost per net MILLION Btu of current fuel?	▶ \$8.500			
141 e	<u></u> >	How many MILLION Btu (net) are required per Day?	60.000			
142		Calculated Average Fuel Cost per day of boiler operation User determines	\$510.00			
143 e	<u></u>	Assumed # days boiler is used per year (for analysis) is? values to input	365			
144		Calculated Average Fuel Cost per Year - current system	\$186,150			
145						
146		to calculate for current system if:				
147		the MILLION Btu (net) required per Day is NOT known				
148		BUT the Average Fuel Cost per Year with the current system IS known				
149 e	<u></u>	What is the average Fuel Cost per Year - current system	 \$186,150			
150 e	<u>></u>	Assumed # days boiler is used per year (for analysis) is?	365			
151		Calculated Average Fuel Cost per day of boiler operation	\$510.00			
152 e	2>	What is the cost per net MILLION Btu of current fuel?	\$8.500			
153		Calculated number of MILLION Btu (net) required per Day?	60.000			

e> Signifies needed input

Bold text shows calculated outputs

FIGURE 3

			С
			\$8.500
			60
a.			\$510.00
			365
			21,900
			\$186,150
		YSTEM	
		iler system	
			\$27.50
		1?	35.0%
			53.8%
		und of wood or bark?	8,250
-		ıel is:	4,950
		n of fuel:	9.900
			80.0%
		system is:	\$3.472
		for the wood system?	\$20,000
		od system %?	95.0%
		system per YEAR is:	20,805
		rational day is:	57.00
		rstem is:	\$72,240
		tem %?	5.0%
183	Calculated MILLION Btu (net) supplied from the ba	ckup system per YEAR	1,095
184 e>	What is the cost per net MILLION Btu of fuel for the bac	kup boiler system?	\$8.500
185	Calculated fuel cost per YEAR for the backup boile		\$9,308
186	Calculated average TOTAL fuel cost per YEAR for	the wood system is:	\$81,547

e> Indicates fields where users are to input requested data. Some of these inputs were calculated in the previous section and simply need to be carried down by the user.

Wood or Bark Fueled System

Information will be entered in the section beginning in row 157. Continuing with the example provided in the spreadsheet, you will see *FIGURE 3* (above) beginning with the information for the current (or alternate) fuel and followed with entries for the wood fueled system.

Required entries for the wood fueled system include delivered fuel cost, moisture content, heating values, and information regarding the back-up boiler system. The final row in the subsection gives the total fuel cost per year for the proposed wood system.

Summary: Average Annual Fuel Cost Savings with Wood/Bark Fueled Boiler System

The previous section estimated the average annual fuel costs of the current (or alternate) and the wood fueled system. The other primary thing to consider as a variable cost is the potential increase in variable cost with a wood system (e.g., labor for fuel loading). Rows 204 and 206 show the annual savings associated with the wood system in both ways (fuel cost only and total variable respectively); see **FIGURE 4** (below).

FIGURE 4

В	С	D	E
202 PRELIMINARY ECONOMIC ANALYSIS - INITIAL ASSESSMENT - ESTIMATION OF AVERA	GE ANNUAL FI	JEL COST	SAVINGS
203 WITH WOOD OR BARK FUELED BOILER SYSTEM			
204 Calculated potential annual savings considering fuel cost differences ONLY	\$104,603		
205			
206 Calculated potential NET annual savings considering BOTH fuel and operational costs:	\$84,603		

Simplified Interpretation of the Initial Results

In the event the calculated potential NET annual savings might be negative (i.e., wood system has a higher annual cost), or if the savings calculated for wood is a very small number, then it probably does not make sense to spend considerable resources in further analysis at this time. However, if your circumstances change significantly, you may wish to investigate this again at a later date. On the other hand, in the event the calculated net annual savings (considering fuel and operational costs) is significant, then the user will probably wish to proceed with some simple payback estimates.

SIMPLIFIED PAYBACK ESTIMATION FOR A WOOD OR BARK FUELED BOILER SYSTEM

Overview

In continuing on to the remaining sections of the spreadsheet program, the user should be comfortable with the assumptions and data inputs required of the previous sections. Also, they should feel additional calculations are warranted to examine the financial feasibility of a wood or bark fueled boiler system in their operations. The following sections expand earlier analysis, however, the user is reminded that calculations still only provide preliminary estimates. If, after running these calculations, it is found that a wood fueled boiler system may appear to be economically attractive, it is then suggested that the user further explore their options with experienced professionals instead of solely relying on this program. In this section, the same data entry format is used. Where indicated, users

provide the requested information in column C and view generated output as bold text. As before, important notes are included directly in the spreadsheet.

The first step in creating a simplified payback estimation for a wood or bark fueled boiler system is to estimate the requirements of such a system. Examining the horsepower requirements of a wood system boiler begins this section. Users are prompted to enter the assumed wood system boiler horsepower. The value entered should be greater than the calculated average requirement. In sizing the wood boiler, the size should be greater than the average daily load to accommodate higher than average demand (e.g., winter season versus summer season load). However, the boiler size cannot be made so large that the minimum load is a very small percentage of the total capacity. Wood fueled boilers do not operate well at very low loads. This underscores the need to involve trained professionals in the analysis.

A table in this section beginning at row 218 provides boiler information. For a given boiler size, this table provides approximate installed cost estimates for wood fueled boilers designed to burn either green wood/bark fuel or dry wood/bark fuel. The table provides rough estimates that will not precisely match most wood/bark fueled boiler system costs. Also, it is important to remember these average costs will change over time. Consequently, these are only generalized estimations of what might be expected as a cost for an installed wood/bark fuel boiler system including the low pressure steam boiler, the fuel stoker and combustion device, flue gas cleaning system, steam piping with water side auxiliaries, assembly, installation, start-up, and operator training. As a rule of thumb, for each 50 horsepower of the boiler system, an area of approximately 2,000 cubic feet is required for wood fuel receiving, metering, and storage for a three-day fuel supply.

Where a wood or bark fueled system is being considered as an alternate to another system, which would need to be installed anyway (e.g., the existing boiler needs to be replaced and the choice is between a wood fueled system or other non-wood fueled system), this is an incremental investment. In this example, the difference in the annual operational cost (savings) associated with the wood or bark fuel would be considered against the difference in the total investment associated with the two systems (i.e., the incremental investment in the wood system). However, if the existing system is in good condition, has considerable remaining life, and does not currently require major (costly) repairs to extend the system life, then the investment in the wood system is essentially the full cost of the wood system (less any salvage value, plus any savings associated with avoided repairs immediately needed on the existing system). This is a very simplified explanation of determining values to be considered in investment, many professions including business and engineering have extensive training in this area. The professional assisting with follow-on analysis should be well versed in this. Also, when considering investment alternatives such as different types of boilers, it is desirable that the economic lives of the two alternatives be the same. Otherwise it will be necessary for the analyst to make appropriate adjustments.

This part of the spreadsheet does a simple "payback" analysis. Payback analysis is often used in preliminary analyses for many reasons. Chief among these – it is simple. Payback estimates the number of years (periods) that would be required to recoup the investment. There are some technical problems associated with payback analysis (including that it does not consider the time value of money). Consequently, payback analysis should not be used as sole decision criteria. Following the example provided, the next two entry prompts ask users to enter the "Estimated Incremental Investment for the Wood or Bark Boiler System" and "The Maximum 'Payback' Period (in Years) Required to Recover Incremental Investment." Desired calculated output, as always, appears as bold text and numbers.

The first of these results is the payback period (in years) for the estimated incremental investment (cell C 271). What this means in this example is that the incremental investment of \$200,000 would be recovered (without considering time value of money) in about 2.4 years.

The second of these results is a value for the estimated maximum incremental investment that could be justified for the wood or bark boiler system (value in cell C 275). What this means is that for the maximum acceptable payback period as specified by the decision-maker (in this example seven years) a maximum incremental investment of about \$590,000 could be justified. (If only a shorter payback period could be accepted, then the maximum acceptable investment would be smaller.)

The following two interpretations can be applied to the generated output:

1. If, according to the decision criteria being used, the payback period required to recover the incremental investment is excessively long, then the operational cost savings associated with a wood or bark fueled boiler does not likely justify the investment at this time. Likewise, if according to the maximum payback period you would be willing to accept, the maximum incremental investment is unrealistically low, then the operational cost savings associated with a wood or bark fueled boiler does not likely justify the investment at this time. Assuming as a result of analysis the wood fueled system is rejected, if circumstances change (e.g., the existing system fails, must be replaced, costs of operation increase significantly, or major facility renovations are being considered), then perhaps the analysis of a wood or bark fueled system should be reconsidered at that time.

2. If, according to the decision criteria being used, the payback period required to recover the incremental investment is short enough, then the operational cost savings associated with a wood or bark fueled boiler could likely justify the required incremental investment at this time. Similarly, if according to the maximum payback period you would be willing to accept, a realistic value for incremental investment is acceptable, then the operational cost savings associated with a wood or bark fueled boiler could justify the required incremental investment at this time. If this is the case, further analysis is justified.

Follow-on Preliminary Assessment

In this section, the spreadsheet program builds further on previous sections. Here the program will provide a fairly detailed estimate of operations for a 20-year analysis period to include the net present value of the expected change in after tax net cash flow associated with the wood fueled boiler. This (the NPV of the ATNCF) is the final calculation at the end of the spreadsheet. Unlike the payback method, this does include an interest cost of capital which considers the time value of money. This section also includes much more detailed analysis to consider the effects of loans, depreciation, taxes and the changes in an array of key variables over time. Users with a familiarity of this type of analysis will find this section straightforward. Those without much experience will want to pay close attention to the prompts in the spreadsheet.

For a user continuing on, it is recommended to scan the spreadsheet for an appreciation of the information required for the follow-on assessment. On rows where the code "e>" or "e>>" is shown in column A, an entry is to be made in one or more columns. In some areas, entries may be required in 20 columns for a single row. This reflects a 20-year analysis. As before, entry numbers in the rows are included only for illustrative purposes. They should not be considered as suitable estimates for your analysis. (The exception is where data calculated in your initial assessment above is shown and clearly labeled as such.)

The user should realize that this section of the spreadsheet is much more technical than the initial assessment section, and it requires some very specific entry assumptions. As a result, many users comfortable with the initial assessment section of the spreadsheet may desire expert assistance to continue with the follow-on section, or to seek expert assistance in checking assumptions and overall analysis.

To continue, follow the "**e>>**" prompts and enter all the requested data accurately for your company.

The first subsection utilizes employee-related data inputs as they pertain to existing or alternate fueled boiler systems. (For illustrative purposes, the spreadsheet displays what is seen in **FIGURE 5** found at the bottom of page 8.)

The second subsection applies to wood or bark fueled systems and, once completed, allows for comparisons between systems. This section proceeds in the same manner as the previous one by utilizing user inputs to generate necessary output.

Upon entering the requested data, the user is presented with a summary section providing detailed information about each boiler system. For convenience, results are shown in both monetary (U.S. dollars) and the percentage each criterion represents to the total payroll.

With these subsections completed, the program provides the estimated annual wood or bark fueled boiler related labor costs for the first full year of operation. These results appear in bold text beginning in cell C 374. Continuing from here, other costs of wood fueled boiler operations are examined. The program is building on previous calculations and using them to generate related outputs. For some variables, the spreadsheet has the user provide estimates for each year in the 20-year period of analysis. This permits change over time in variables such as fuel costs, other variable costs, fixed costs, and load. The first year (or period) of the analysis is likely to be a "partial year" as the boiler system would not likely be in place on day one of the year. Consequently, the program treats year two as the first full year.

Summary of Inputs Into Analysis for Period #2 (First Full Year)

The items in column E under the label "ENTRY" are reflecting a relative address of items which are in column C under the label "CALCULATED." If you change nothing, these "calculated" values will become the "entry" values for the first full year (period or year #2) of the following financial analysis. If adjustments to first full year values (year #2) are desired, they can be made directly within the "ENTRY" area of column E. This structure with an attached link that may be easily broken and re-attached, facilitates easy heuristic ("What if?") analyses. After an initial run, the analyst may wish to change some parameters of the economic analysis without changing the prior calculations. This breakable link allows that to be done easily but retains the calculated original value for comparison and quickly identifies that such heuristic experimentation is being conducted. Thus, any or all of the key assumption variables calculated for use in the analysis may be directly modified to a desired value (for illustration, see **FIGURE 6** found on page 9).

Period Inputs into the Economic Model

The data under "ENTRY" in column E will automatically be reflected as the values for the first full year (Year #2) in the subsequent entries.

An entry is required in all other cells of each row in each column, for items in Year #1 and Year #3 through Year #20 with entry as a percent of the item value entered for Year #2. The percentage change entry format convention is used because it is generally easier. These data will be transformed to values in the "KEY PRODUCTION DATA" section.

FIGURE 5

	Α	В	С	D	E	F
314		BOILER RELATED PAYROLL DATA - EXISTING OR ALTERNATE SYSTEM				
315	e>>	Average # of employees working with boiler related duties 1st shift			0.25	
316	e>>	Average # of employees working with boiler related duties 2nd shift			0	
317	e>>	Average # of employees working with boiler related duties 3rd shift			0	
		Average # of employees working with boiler related duties 4th shift			0	
319		AVERAGE # OF BOILER RELATED EMPLOYEES, ALL SHIFTS COMBINED			0.25	
320		Assumed # days boiler is used per year (for analysis) is?			365	
	e>>				245	
322	e>>	Average base hourly wage of boiler related employees			\$10.25	
323	e>>	Fringe benefits for employees as a % of base hourly wage			25.00%	
324	e>>	Overtime premium for employees as a % of base hourly wage			50.00%	
		Fringe benefits for overtime hours a % of the overtime hourly wage			20.00%	
326	e>>	Normal # of boiler related paid hours per shift (not including overtime)			3.00	
		Average # of overtime hours per boiler related employee per month boiler is operated			4.00	
328		AVERAGE # OF OVERTIME HOURS PER BOILER RELATED EMPLOYEE PER YEAR			48.00	
329	e>>	Other boiler related payroll expenses in total dollars per year			\$0	
330						
331		SUMMARY OF ESTIMATED ANNUAL BOILER RELATED LABOR COSTS FIRST FULL	YEAR - EXIS	TING OR A	LTERNATE	SYSTEM
332		ANNUAL PAYROLL BREAKDOWN	DOLLARS	PERCENT		
333		BASE WAGES	\$1,883	73%		
334		FRINGE BENEFITS	\$471	18%		
335		OVERTIME WAGES	\$185	7%	-	1
336		OVERTIME FRINGE	\$37	1%		
337		OTHER PAYROLL	\$0	0%		
338		TOTAL PAYROLL	\$2,576	100%		
339		BOILER RELATED LABOR \$/DAY OF BOILER OPERATION	\$7			

e>> Insert requested data

The program runs calculations and displays results here -

FIGURE 6

АВ	BCC		F G			
444		e>> (IMPORTA	e>> (IMPORTANT - see note above)			
445	CALCULATED	ENTRY				
446 e>> MILLION Btu (net) that are required per YEAR is:	21,900	21,900				
447 e>> Cost per net MILLION Btu of current (or alternate) fuel is:	\$8.50	\$8.50				
448 e>> Cost per net MILLION Btu of wood or bark boiler system is:	\$3.47	\$3.47				
449 e>> Cost per net MILLION Btu of fuel for the backup boiler system?	\$8.50	\$8.50				
450 e>> Fraction of annual Btu needs to be supplied by the wood system is:	95%	95.00%				
451 e>> Increase in Total Payroll With the Wood Fueled System Per MILLION Btu Net	\$0.649	\$0.65				
452 e>> Increase in Total Other Variable Costs With the Wood Fueled System Per MILLION Btu Net	\$0.276	\$0.28				
453 e>> Increase in Total Fixed Costs With the Wood Fueled System in Total \$/Year	\$400	\$400				

Capital Investments and Simplified Estimation of Depreciation

Where an analysis is conducted as an incremental analysis, the incremental investment associated with the wood or bark fueled system should be used.

Note that the model estimates depreciation for investments in the different property classes using the MACRS GDS system with 200% DB and half-year convention. To do this, the total INITIAL investment in the different property classes is simply entered in column C as appropriate.

If any other depreciation method is desired, the appropriate values for non-depreciable property and working capital should still be entered, and any other appropriate depreciation values may be directly entered in either of the two rows labeled "OTHER DEPRECIATION IN YEAR."

In the capital investment summary, note that all standard Year #1 investments, including Year #1 working capital, are entered automatically. Total investments in all other years (if any) must be manually entered.

SUMMARY

In the section titled "FINANCIAL SUMMARY ANALYSIS" data provided and key variable items calculated from the data are used. Also, the user enters data for four additional criterion. Calculations for criteria listed in bold text appear as yearly estimates extended out to 20 years. Loan summary information is also calculated at this point and is displayed for easy user reference.

The last section of the spreadsheet (illustrated in *Figure 7* and *Figure 8* found on page 10), is **"CALCULATION OF NET PRESENT VALUE OF** AFTER TAX NET CASH FLOW ASSOCIATED WITH WOOD OR BARK FUELED SYSTEM." In this section, the only user input is the "Cost Of Capital to use as 'i' " (discount interest rate) which will be used in the NPV calculation. The result of the initial assessment section of the spreadsheet provided a simplistic decision criteria of payback periods. The result of the follow-on section provides a much more sophisticated decision criteria, and includes parameters of the time value of money in establishing a cost of capital, and the increased sophistication of depreciation, taxation, change of variables over time, etc. In interpreting the decision criteria results of the net present value, a positive number would justify the project. Within payback analysis, a savings with the wood system could appear attractive but ignore the cost of capital or time value of money. Within NPV analysis, the result hinges heavily on the discount rate. Consequently, a large assumed cost of capital requires commensurate increase in savings as an offsetting factor. Within NPV analysis, a negative number could be achieved in circumstances that exhibit savings with the wood fueled system that is insufficient to recover the investment plus interest.

FIGURE 7

	A	В	С	D	E	F	G	Н
551		FINANCIAL SUMMARY ANALYSIS						
552			YEAR #1	YEAR #2	YEAR #3	YEAR #4	YEAR #5	YEAR #6
553		MILLION Btu (net) THAT ARE REQUIRED PER YEAR IS:	16,425	21,900	21,900	21,900	21,900	21,900
554		FUEL COST FOR THE YEAR IF CURRENT OR ALTERNATE FUEL WAS USED	* \$139,613	\$186,150	\$193,596	\$201,340	\$209,393	\$217,769
555		TOTAL FUEL COST WITH THE WOOD FIRED SYSTEM (AND BACKUP)	\$73,548	\$81,547	\$84,809	\$88,201	\$91,729	\$95,399
556		ANNUAL INCREASE IN VARIABLE LABOR COST WITH WOOD SYSTEM	\$10,655	\$14,207	\$14,775	\$15,366	\$15,981	\$16,620
557		ANNUAL INCREASE IN OTHER VARIABLE COST WITH WOOD SYSTEM	\$4,538	\$6,050	\$6,232	\$6,418	\$6,611	\$6,809
558		OPERATIONAL COST SAVINGS ASSOCIATED WITH THE WOOD SYSTEM (\$/YEAR)	\$50,872	\$84,346	\$87,780	\$91,354	\$95,072	\$98,941
559		OPERATIONAL COST SAVINGS FOR THE WOOD SYSTEM (%/ ALTERNATE FUEL FOR YEAR)	36%	45%	45%	45%	45%	45%
	e>>	other associated net revenue (or operational cost savings) subject to normal tax	\$0	\$0	\$0	\$0	\$0	\$0
561		TOTAL FUEL COST SAVINGS WITH THE WOOD FIRED SYSTEM (AND OTHER REVENUE)	\$66,065	\$104,603	\$108,787	\$113,139	\$117,664	\$122,371
562		TOTAL INCREASE IN NON-FUEL VARIABLE COST/YEAR WITH WOOD SYSTEM	\$15,193	\$20,257	\$21,007	\$21,785	\$22,592	\$23,429
563		TOTAL INCREASE IN FIXED COST/YEAR WITH WOOD SYSTEM	\$400	\$400	\$412	\$424	\$437	\$450
564		INTEREST ON LOAN	\$15,527	\$14,443	\$13,275	\$12,016	\$10,659	\$9,198
565		INCREASE IN NET PROFIT BEFORE DEPREC. & TAX (SAVINGS WITH WOOD SYSTEM)	\$34,946	\$69,503	\$74,094	\$78,914	\$83,976	\$89,293
566		TOTAL DEPRECIATION INCREASE ASSOCIATED WITH WOOD SYSTEM	\$30,580	\$52,180	\$36,900	\$26,132	\$19,012	\$18,416
567		CHANGE IN TAXABLE INCOME ASSOCIATED WITH WOOD SYSTEM	\$4,366	\$17,323	\$37,194	\$52,782	\$64,964	\$70,877
568		ТАХ	\$1,834	\$7,276	\$15,621	\$22,168	\$27,285	\$29,768
569		CHANGE IN (operational) AFTER TAX PROFIT (LOSS) DUE TO WOOD SYSTEM	\$2,532	\$10,048	\$21,572	\$30,613	\$37,679	\$41,109
570		CHANGE IN (operational) AFTER TAX NET CASH FLOW WITH WOOD SYSTEM	\$33,112	\$62,228	\$58,472	\$56,745	\$56,691	\$59,525
571	e>>	other net revenue or equivalent positive cash flows NOT subject to capital gains tax	\$0	\$0	\$0	\$0	\$0	\$0
572	e>>	other net revenue subject to capital gains tax	\$0	\$0	\$0	\$0	\$0	\$0
573		CAPITAL GAINS TAX	\$0	\$0	\$0	\$0	\$0	\$0
574		CHANGE IN AFTER TAX NET CASH FLOW WITH WOOD SYSTEM	\$33,112	\$62,228	\$58,472	\$56,745	\$56,691	\$59,525
575		MINIMUM LOAN PRINCIPAL REPAYMENT	\$13,962	\$15,046	\$16,214	\$17,473	\$18,829	\$20,291
576	e>>	Additional loan principal repayment	\$0	\$0	\$0	\$0	\$0	\$0
577		CHANGE IN NET ADDITION TO RETAINED EARNINGS WITH WOOD SYSTEM	\$19,150	\$47,182	\$42,259	\$39,273	\$37,862	\$39,234

Actual spreadsheet shows Years 1 through 20

FIGURE 8

	Α	В	С	D	E	F	G	Н
580		SUMMARY OF LOAN INFORMATION						
581			YEAR #1	YEAR #2	YEAR #3	YEAR #4	YEAR #5	YEAR #6
582		BEGINNING PRINCIPAL DUE	\$200,000	\$186,038	\$170,992	\$154,779	\$137,306	\$118,477
583		MINIMUM PRINCIPAL REPAYMENT	\$13,962	\$15,046	\$16,214	\$17,473	\$18,829	\$20,291
584		ADDITIONAL PRINCIPAL REPAYMENT	\$0	\$0	\$0	\$0	\$0	\$0
585		ENDING PRINCIPAL DUE	\$186,038	\$170,992	\$154,779	\$137,306	\$118,477	\$98,186
586		INTEREST PAYMENTS	\$15,527	\$14,443	\$13,275	\$12,016	\$10,659	\$9,198
587								
588								
589								
590		CALCULATION OF NET PRESENT VALUE OF AFTER TAX NET CASH FLOW ASSOCI	ATED WITH WO	DOD OR B	ARK FUELED	SYSTEM		
591								
592		TOTAL (INCREMENTAL) INITIAL INVESTMENT INCLUDING WORKING CAPITAL			\$215,000			
593		APPROX. NET PRESENT VALUE OF TOTAL INVESTMENTS ALL YEARS			\$215,000			
594	e>>	Cost Of Capital to use as "i" in NPV Calculation			20.00%			
595		PRESENT VALUE OF AT NET CASH FLOW (ATNCF NPV)			\$283,411			
596		SUM OF DEPRECIATION (TOTAL FOR YEARS 1.20)			\$210,000			
597		PRESENT VALUE OF RESIDUAL ASSET SUBJECT TO CAPITAL GAINS TAX (Year 20)			\$438			
598		PRESENT VALUE OF INITIAL WORKING CAPITAL			\$104			
599		APPROXIMATE FINAL NPV OF AFTER TAX NET CASH FLOW			\$68.954			



GLOSSARY

Alternate Fuel

A commercially available resource capable of providing energy but different from that currently in use for a given operation.

British Thermal Unit (Btu)

The quantity of heat which is required to increase the temperature of one pound of water one degree Fahrenheit.

Heat of Combustion

The quantity of heat that is released when a measurable amount of a combustible substance is burned to form incombustible substances. Examining the differences in heats of combustion for different fuel sources is a way to explore which is more economical.

Incremental Investment

The difference in the costs of two systems. For example, the difference between wood boiler systems costs and an alternate fuel boilers costs (e.g., the excess investment cost associated with the wood fueled system).

Moisture Content (MC) -Green Basis

The percentage of the total weight (of wood plus water in the wood) that is water. This varies widely depending on the species and if the wood has dried somewhat after harvest. In general, a reasonable estimate for many hardwoods is about 44% to 45% MC on a green basis. Some dense hardwoods are lower. Alternatively, many softwoods and low density hardwoods such as aspen can exceed 50% MC.

Moisture Content (MC) -Ovendry Basis

The total moisture (water in wood) as a percentage of the weight of ovendry wood. Frequently, the ovendry basis MC percent will exceed 100% (this simply means the water in green wood weighs more than the dry wood). The ovendry basis MC varies widely with species, and also within species (e.g., if the wood has dried after harvest, etc.). About 80% ovendry MC is a reasonable estimate for many hardwoods. Many softwoods and hardwoods such as aspen can exceed 100%.

Net Present Value (NPV)

The benefits less the costs of a given item over time. (A current value assigned to net benefits and derived using a discount rate.)

APPENDIX: DISCUSSION OF SAMPLE WOOD FUELED BOILER FEASIBILITY ANALYSIS CASE

The following sample case represents an actual case study analysis conducted in the Lake States region of the United States. To maintain confidentiality, the company name and specific location is not included, and the company-sensitive circumstances have been slightly altered in the form of either data inputs or some assumptions related to costs, sizes, and loads. These slight modifications are sufficient to disguise company identity and provide confidentiality. However, in aggregate they are not sufficient to significantly alter the case study results for any of these illustrations. The case analysis provides the sample entries that are used in the standard model form of the "Wood Fueled Boiler Financial Feasibility" spreadsheet program.

The case was an analysis conducted for a secondary forest products manufacturer. The company has lumber dry kiln capacity of approximately 200 MBF (multiple kilns, all used to dry hardwood lumber). This capacity is currently served by an approximately 200 horsepower natural gas boiler which can also be fueled by kerosene. The existing boiler is of an age and in a condition where it is not desirable as a primary boiler, but it is suitable as a back-up boiler. Additional capacity for potential near-future kiln expansion is desired. Fuel costs for existing fuels are typical for an industrial customer of that size in the area. Wood fuel for the wood fueled boiler would primarily be purchased from local companies in a well-developed local market with adequate supply in a green/dry mixture.

An estimated 60 million (net) Btus are required per day (year-round) on average. The cost per net million Btus is estimated to be approximately \$8.50 at current natural gas prices with the existing boiler system at average efficiency. Assuming a delivered price of \$27.50 per green ton of wood fuel at an average of approximately 35% moisture content (green basis), the fuel cost for the wood fired boiler is estimated to be less than approximately \$3.50 per net million Btus, or about 40% of the fuel cost using natural gas.

Assuming the existing natural gas fired boiler is due to be replaced regardless, and the existing boiler will be kept as a back-up, by installing a wood fueled boiler (versus natural gas fueled boiler), the incremental additional investment in the wood boiler (in excess of the cost of a gas boiler of the same size) would be equal to approximately 50% of the cost of the wood fueled system. The difference in investment alternatives is the basis for investment costs to compare the operational savings which are in excess of approximately \$100,000 per annum at current loads based on fuel costs only, or about \$85,000 per year when some additional operational costs are also considered (NOTE: Kiln expansion would increase annual fuel cost savings).



APPENDIX: DISCUSSION OF SAMPLE WOOD FUELED BOILER FEASIBILITY ANALYSIS CASE

(Continued)

Assuming an approximately 150 horsepower wood fueled boiler would be installed (capable of meeting average load of existing kilns while at approximate 50% of capacity and offering room for kiln expansion to at least 300 MBF), and assuming the wood fueled system would represent an incremental investment of about \$200,000, the estimated payback on the wood fueled system would be less than three years. Even assuming the full cost of investment (versus incremental cost) is used as the basis of investment in the analysis, the payback period would be less than five years – and in both cases, if kiln capacity were expanded, the payback periods would be reduced. Within the follow-on preliminary assessment section of the model, the data used in most cases represent and initial "best-guess" with an effort to be somewhat conservative as a starting point, taking care to not consciously favor the installation of the wood fueled boiler. The net result of this 20-year analysis was still very favorable, reflecting a significant positive net present value, even assuming a 20% overall cost of capital (discounting interest rate) in the analysis. This is, of course, is only a starting point, and the inputs would be refined in working with engineering professionals and others if the project is taken to the next steps of design and planning.

THIS MANUAL WAS PREPARED BY

Robert Govett

Professor College of Natural Resources, University of Wisconsin-Stevens Point

Scott Bowe

Assistant Professor Department of Forest Ecology and Management, University of Wisconsin-Madison

Terry Mace

Forest Utilization and Marketing Specialist Wisconsin Department of Natural Resources -Division of Forestry

Steve Hubbard

Consultant Hubbard Forest Solutions, LLC

John (Rusty) Dramm

Utilization Specialist USDA Forest Service, State and Private Forestry

Richard Bergman

Research Chemical Engineer USDA Forest Service

Funding for this manual was provided by the

Rural Development Through Forestry Program, USDA Forest Service State and Private Forestry, Morgantown, West Virginia.









